APPLICATION FOR TELETHERAPY AUTHORIZATION

INSTRUCTIONS: A complete teletherapy application consists of this form, the report of the shielding consultant, and drawings of the proposed facility and its environs. Applications should be submitted in duplicate to **Radiologic Health Branch**, **Radioactive Materials Licensing**, **MS 7610**, **P.O. Box 997414**, **Sacramento**, **CA 95899-7414**.

1. This application is submitted by	License No		
() a. For a new license for a teletherapy unit: Mfr			
() b. For an amendment to add a teletherapy unit: Mfr	Model		
() c. For an amendment for a new source in the present telet	herapy unit		
Description of proposed source capsule			
a. Manufacturer	Model		
b. Isotope Source strength (r/hr @ 1m)			
b. isotope Source strength (i/iii & iiii)	Source diam	leter (CIII)	
3. Description of teletherapy mount			
Rotational	Vertical Column		
() a. No integral primary barrier	() d. Head swivels to side only		
() b. Beam may bypass integral primary barrier	() e. Head tilts outward only		
() c. Beam always intercepted by integral primary barrier	() f. Head swivels and tilts out		
4. Participating firms and consultants			
a. Architect	Address		
b. Shielding consultant	Address		
c. Vendor	Address		
d. Installer	Address		
e. Future service	Address		
f. Survey and calibration	Address		
g. Leak testing	Address		
5. Personnel exposure with present source			
Names of Individuals	<u>Last Quarter</u>	<u>Last Year</u>	
a			
b			
C			
d. Actual hours of machine on-time			

f. Present strength of source in curies _____

Names of Individuals	sed source	First	: Quarter Fi	rst Year	
a					
b					
C					
d. Hours of expected machine on-time					
e. Dosimetry supplier		Dosir	Dosimetry change interval		
Operating factors					
a. Maximum expected workload in r/weel	at 1 meter from so	ource:			
b. Maximum feasible workload in r/week	at 1 meter from sou	rce:	_		
c. Permissible weekly exposure from tele	therapy unit only: _				
d. Patient source to skin treatment distan	ces normally to be	used			
(1) cm distance will b	e used	% of time			
(2) cm distance will b	e used	% of time			
(3) cm distance will b	e used	% of time			
e. Use factors (primary beam direction fa	ctors)				
(1) North wall	(4) So	uth wall			
(2) East wall	(5) We	5) West wall			
(3) Ceiling	(6) Flo	or			
f. Distances in feet with beam directed d	ownward and the so	ource positioned at	average height		
(1) Source to North wall	(4) So	urce to South wall_			
(2) Source to East wall	(5) So	(5) Source to West wall			
(3) Source to ceiling	(6) So) Source to floor			
g. Occupancy factors for surrounding are	a				
Area Nature of o	occupancy	<u>Factor</u>	<u>Distance</u>	Controlled?	
(1) Beyond North wall					
(2) Beyond East wall					
(3) Beyond South wall					
(4) Beyond West wall					
(5) Above ceiling					
(6) Below floor					
		t Paragraphy to	. (Parla Control	
cense is in the name of an institution, res st sign below.		flicense is in name Officer must sign be	of an individual, Ra low.	alation Safety	
					
OFFICIAL	DATE	RADIATION SA	FETY OFFICER	DATE	